



# Test Report : DKM30F-12N

---

30W 2"x1" Package DC-DC Regulated Converter

## ■ DESIGN VERIFY TEST

Output Function Test

Input Function Test

Protection Function Test

## ■ SAFETY TEST

Safety Test

## ■ RELIABILITY TEST

Environment Test

Other Test

## DESIGN VERIFY TEST

### OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDITC
1	VOLTAGE ACCURACY	-2% ~ +2 %	I/P:12VDC O/P:FULL LOAD Ta:25°C	-0.05% +0.18%	P
2	RIPPLE & NOISE	150 mVp-p	I/P:12VDC O/P:FULL LOAD Ta:25°C	25 mV 23mV	P
3	LINE REGULATION	-0.2% ~ +0.2%	I/P:9VDC~36VDC O/P:FULL LOAD Ta:25°C	-0.03% ~ +0.03% +0.01% ~ +0.03%	P
4	LOAD REGULATION	-0.5% ~ +0.5%	I/P:12VDC O/P: 0% LOAD~FULL LOAD Ta:25°C	-0.04% ~ -0.07% -0.02% ~ +0.12%	P

### INPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDITC
1	INPUT VOLTAGE RANGE	9 VDC ~36 VDC	I/P:TESTING O/P:FULL LOAD Ta:25°C	8.1 VDC ~ 36 VDC	P
2.	EFFICIENCY	87%	I/P:12VDC O/P:FULL LOAD Ta:25°C	87.9%	P
3	DC CURRENT	2850 mA / FULL LOAD 28 mA / NO LOAD	I/P:12VDC O/P:NO / FULL LOAD Ta:25°C	2833 mA / FULL LOAD 26.4 mA / NO LOAD	P

### PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDITC
1	SHORT PROTECTION	CONTINUOUS	I/P:36VDC O/P:FULL LOAD Ta:25°C	AUTOMATIC RECOVERY	P
2	OVER LOAD PROTECTION	110~230%	I/P:12VDC O/P:TESTING Ta:25°C	159.1 % HICCUP MODE AUTO-RECOVER	P
3.	INPUT OVER VOLTAGE	40VDC typ.	I/P:TESTING O/P:FULL LOAD Ta:25°C	38.7 VDC SHTDOWN OUTPUT VOLTAGE AUTO-RECOVER	P

## CONTROL FUNCTION TEST

TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1 REMOTE CONTROL	Power on : >2.5~5.0Vdc or open ircuit Power off : R.C <1.0Vdc or short	I/P:12VDC O/P:FULL LOAD Ta:25°C	Power on : R.C>1.1Vdc or Open Power off : R.C<0.9Vdc or Short	P

## SAFETY TEST

### SAFETY TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDITC
1	WITHSTAND VOLTAGE	I/P-O/P:3.0K VDC/min	I/P-O/P:3.0K VDC/min Ta:25°C	I/P-O/P: 0.002mA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P:500VDC>100MΩ	I/P-O/P:500 VDC Ta:25°C	I/P-O/P>100MΩ NO DAMAGE	P

## RELIABILITY TEST

### NVIRONMENT TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT										
1	TEMPERATURE RISE TEST	1. ROOM AMBIENT BURN-IN : 8HRS I/P:12VDC O/P:FULL LOAD Ta=25°C 2. HIGH AMBIENT BURN-IN : 8HRS I/P:12VDC O/P:FULL LOAD Ta=60°C 3. HIGH AMBIENT BURN-IN : 8HRS I/P:12VDC O/P:50% LOAD Ta=80°C			P										
		<table border="1"> <thead> <tr> <th>NO</th> <th>Position</th> <th>1</th> <th>2</th> <th>3</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>CASE</td> <td>66.6°C</td> <td>98.3°C</td> <td>98.2°C</td> </tr> </tbody> </table>			NO	Position	1	2	3	1	CASE	66.6°C	98.3°C	98.2°C	
NO	Position	1	2	3											
1	CASE	66.6°C	98.3°C	98.2°C											
2	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 4 HOURS	I/P:12VDC O/P: FULL LOAD Ta= -40°C	TEST : OK	P										

## OTHER

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDITC
1	MTBF	MIL-HDBK-217F,GB,25°C TOTAL FAILURE RATE : 3.95557 M.T.B.F : 254,092.80 HRS			P

TEST RESULT	TESTER	APPROVAL
PASS	ARCHEN HSIAO	PETER CHENG