



Test Report: GSM40A48

40W AC-DC Reliable Green Medical Adaptor

■ DESIGN VERIFY TEST

- Output Function Test
- Input Function Test
- Protection Function Test
- Control Function Test
- Component Stress Test

■ SAFETY & E.M.C. TEST

- Safety Test
- E.M.C. Test

■ RELIABILITY TEST

- ENVIRONMENT TEST

■ DESIGN VERIFY TEST

OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	RIPPLE & NOISE	V1 : 150 mVp-p (Max)	I/P : 230VAC O/P : FULL LOAD Ta : 25°C	V1 : 120 mVp-p (Max)	P
2	OUTPUT VOLTAGE TOLERANCE	V1 : -2.5%~ +2.5% (Max)	I/P : 80 VAC / 264 VAC O/P : FULL/ MIN LOAD Ta : 25°C	V1 : -0.1%~ 0.17%	P
3	LINE REGULATION	V1 : -1%~ +1% (Max)	I/P : 100 VAC ~ 264 VAC O/P : FULL LOAD Ta : 25°C	V1 : -0.04%~ 0.07%	P
4	LOAD REGULATION	V1 : -2.5%~ +2.5% (Max)	I/P : 230 VAC O/P : FULL ~MIN LOAD Ta : 25°C	V1 : -0.08%~ 0.17%	P
5	SET UP TIME	230VAC : 1000 ms (Max) 115VAC : 1500 ms(Max)	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	230VAC/ 568 ms 115VAC/ 1130 ms	P
6	RISE TIME	230VAC : 30 ms (Max) 115VAC : 30 ms (Max)	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	230VAC/ 16.1 ms 115VAC/ 19.5 ms	P
7	HOLD UP TIME	230VAC : 50 ms (TYP) 115VAC : 24 ms (TYP)	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	230VAC/ 57.6 ms 115VAC/ 30.1 ms	P
8	OVER/UNDERSHOOT TEST	< ±5%	I/P : 230 VAC O/P : FULL LOAD Ta : 25°C	TEST : <5%	P
9	DYNAMIC LOAD	V1 : 4800 mVp-p	I/P : 230 VAC (1).O/P : FULL /Min LOAD 90%DUTY/ 1KHZ (2).O/P : FULL /Min LOAD 90%DUTY/ 3KHZ (3).O/P : FULL /Min LOAD 90%DUTY/ 5KHZ (4).O/P : FULL /Min LOAD 50%DUTY/ 120HZ Ta : 25°C	(1) 246 mVp-p (2) 196 mVp-p (3) 188 mVp-p (4) 270 mVp-p	P

INPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
----	-----------	---------------	----------------	--------	---------

1	INPUT VOLTAGE RANGE	80VAC~264 VAC	I/P : TESTING O/P : FULL LOAD Ta : 25°C	59.8 V~264V TEST : OK	P
			I/P : LOW-LINE-3V= 77 V HIGH-LINE+15%=300 V O/P : FULL/MIN LOAD ON : 30 Sec . OFF : 30 Sec 10MIN (AC POWER ON/OFF NO DAMAGE)		
2	INPUT FREQUENCY RANGE	47HZ ~63 HZ NO DAMAGE OSC	I/P : 80 VAC ~ 264 VAC O/P : FULL~MIN LOAD Ta : 25°C	TEST : OK	P
3	EFFICIENCY	91 % (TYP)	I/P : 230 VAC O/P : FULL LOAD Ta : 25°C	91.45 %	P
4	INPUT CURRENT	230V/ 0.5 A (TYP)	I/P : 230 VAC	I = 0.371 A/ 230 VAC	P
		115V/ 1 A (TYP)	I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	I = 0.678 A/ 115 VAC	
5	INRUSH CURRENT	230V/ 60 A (TYP)	I/P : 230 VAC/115VAC	I = 41.570 A/ 230 VAC	P
		115V/ 30 A (TYP) COLD START	O/P : FULL LOAD Ta : 25°C	I = 22.214 A/ 115VAC	
6	LEAKAGE CURRENT	< 90 uA/ for earth leakage current	I/P: 264 VAC O/P:Min LOAD Ta:25°C	L-FG 85.5 uA N-FG 85.5 uA	P
		< 90 uA/ for touch leakage current	I/P: 264 VAC O/P:Min LOAD Ta:25°C	L-V- 85.6 uA N-V- 85.6 uA	
7	NO LOAD CONSUMPTION	< 0.1 W	I/P : 240VAC O/P : NO LOAD Ta : 25°C	< 0.069 W	P

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	OVER LOAD PROTECTION	105 % ~160 %	I/P : 230 VAC I/P : 115 VAC O/P : TESTING Ta : 25°C	137.7 %/ 230 VAC 135.7 %/ 115 VAC Protection type : Hiccup mode, recovers automatically after fault condition is removed	P
2	OVER VOLTAGE PROTECTION	CH1 : 50.4 V ~ 64.8 V	I/P : 230 VAC I/P : 115 VAC O/P : MIN LOAD Ta : 25°C	58.2 V/ 230 VAC 58.3 V/ 115 VAC Protection type : Shut down o/p voltage, re-power on to recover	P
3	SHORT PROTECTION	SHORT EVERY OUTPUT 1 HOUR NO DAMAGE	I/P : 264 VAC O/P : FULL LOAD Ta : 25°C	NO DAMAGE Hiccup Mode	P

CONTROL FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	ERP STEP2 COMPLIANT	LEVEL V	I/P: 230 VAC/115VAC O/P:100/75/50/25% LOAD Ta:25°C	230V 90.5 % 115V 89.9 %	P

COMPONENT STRESS TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	Power Transistor (D to S) or (C to E) Peak Voltage	Q1 Rated : 700 V 10 A	I/P : High-Line +3V = 267 V O/P : (1)Full Load Turn on (2) Output Short (3)Full load continue Ta : 25°C	(1) 608 V (2) 652 V (3) 600 V	P
2	Diode Peak Voltage	D100 Rated : 200 V 10 A	I/P : High-Line +3V = 267 V O/P : (1)Full Load Turn on (2)Output Short (3)Full load continue Ta : 25°C	(1) 185 V (2) 150 V (3) 183 V	P
3	Input Capacitor Voltage	C 5 Rated : 120u /400V/105°C	I/P : High-Line +3V = 267 V O/P : (1)Full Load Turn on /Off (2) Min load Turn on /Off (3)Full Load /Min load Change Ta : 25°C	(1) 376 V (2) 380 V (3) 380 V	P
4	Control IC Voltage Test	U 1 Rated : 28 V	I/P : High-Line +3V = 267 V O/P : (1)Full Load Turn on /Off (2) Min load Turn on /Off (3)Full Load /Min load Change Ta : 25°C	(1) 17.3 V (2) 17.4 V (3) 15.1 V	P
5	CLAMP DIODE	D 1 Rated : 800 V 2 A	I/P : High-Line +3V = 267 V O/P : (1)Full Load Turn on (2) Output Short (3)Full load continue Ta : 25°C	(3) 488 V (4) 408 V (3) 484 V	P

■ SAFETY & E.M.C. TEST

SAFETY TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P : 4 KVAC/min	I/P-O/P : 4.2KVAC/min	I/P-O/P : 1.715 mA	P

		I/P-FG : 2KVAC	I/P-FG : 2.1KVAC Ta : 25°C	I/P-FG : 1.594 mA NO DAMAGE	
2	ISOLATION RESISTANCE	I/P-O/P : 500VDC>100MΩ I/P-FG : 500VDC>100MΩ	I/P-O/P : 500 VDC I/P-FG : 500 VDC Ta : 25°C / 70%RH	I/P-O/P : 9999 MΩ I/P-FG : 9999 MΩ NO DAMAGE	P
3	GROUNDING CONTINUITY	FG(PE) TO CHASSIS OR TRACE < 100 mΩ	40 A / 2min Ta : 25°C / 70% RH	10 mΩ	P

E.M.C TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	HARMONIC	BS EN/EN61000-3-2 CLASS A	I/P : 230 VAC/50HZ O/P : FULL LOAD Ta : 25°C	PASS	P
2	CONDUCTION	BS EN/EN55011 (CISPR11), FCC PART 15 / CISPR22, CAN ICES-3(B)/NMB-3(B) CLASS B	I/P : 230 VAC (50HZ) O/P : FULL/50% LOAD Ta : 25°C	PASS Test by certified Lab	P
3	RADIATION	BS EN/EN55011 (CISPR11), FCC PART 15 / CISPR22, CAN ICES-3(B)/NMB-3(B) CLASS B	I/P : 230 VAC (50HZ) O/P : FULL LOAD Ta : 25°C	PASS Test by certified Lab	P
4	E.S.D	BS EN/EN61000-4-2 AIR:15KV / Contact:8KV	I/P : 230 VAC/50HZ O/P : FULL LOAD Ta : 25°C	CRITERIA A	P
5	E.F.T	BS EN/EN61000-4-4 INPUT: 2KV	I/P : 230 VAC/50HZ O/P : FULL LOAD Ta : 25°C	CRITERIA A	P
6	SURGE	BS EN/EN61000-4-5 INDUSTRY L-N :1KV L,N-FG:2KV	I/P : 230 VAC/50HZ O/P : FULL LOAD Ta : 25°C	CRITERIA A	P
7	Test by certified Lab & Test Report Prepare				

■ RELIABILITY TEST

ENVIRONMENT TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
----	-----------	---------------	----------------	--------	---------

1	TEMPERATURE RISE TEST	<p>MODEL : GSM40A24</p> <p>1. ROOM AMBIENT BURN-IN : 2 HRS I/P : 230VAC O/P : FULL LOAD Ta= 15.3 °C</p> <p>2. HIGH AMBIENT BURN-IN : 2 HRS I/P : 230VAC O/P : FULL LOAD Ta= 48.3 °C</p> <table border="1" data-bbox="502 425 1340 1097"> <thead> <tr> <th>NO</th> <th>Position</th> <th>PART NUMBER</th> <th>ROOM AMBIENT Ta= 15.3°C</th> <th>HIGH AMBIENT Ta= 48.3°C</th> </tr> </thead> <tbody> <tr><td>1</td><td>LF1</td><td>TR1082 6-L2012-W902 18.9m GS</td><td>38.2°C</td><td>68.3°C</td></tr> <tr><td>2</td><td>LF2</td><td>TR1083 W620 52~85m GSM60</td><td>40.6°C</td><td>71.2°C</td></tr> <tr><td>3</td><td>BD1</td><td>BD 4A/800V GLASS UD4KB80</td><td>44.4°C</td><td>74.2°C</td></tr> <tr><td>4</td><td>C5</td><td>120u/400V 105°C 18*31.5 VZ EPT</td><td>39.0°C</td><td>69.5°C</td></tr> <tr><td>5</td><td>D1</td><td>RD 2A/800V GP20K T-52mm</td><td>49.3°C</td><td>79.8°C</td></tr> <tr><td>6</td><td>C40</td><td>C/E 33u/50V UL10Kh 6.3*11 YXM</td><td>44.2°C</td><td>74.9°C</td></tr> <tr><td>7</td><td>D40</td><td>RD 1A/1KV 1N4007GP T-52mm</td><td>43.9°C</td><td>74.7°C</td></tr> <tr><td>8</td><td>T1coil</td><td>MT TF2495-R0 PQ-2620 GSM40-24 B</td><td>48.4°C</td><td>78.2°C</td></tr> <tr><td>9</td><td>T1core</td><td>MT TF2495-R0 PQ-2620 GSM40-24 B</td><td>45.9°C</td><td>75.7°C</td></tr> <tr><td>10</td><td>D100</td><td>SBD STPS20120CT 20A/120V TO220</td><td>53.3°C</td><td>82.4°C</td></tr> <tr><td>11</td><td>C105</td><td>C/E 470u/35V UL7Kh 10*20 KY</td><td>43.7°C</td><td>73.6°C</td></tr> <tr><td>12</td><td>U1</td><td>PWM FAN6756MRMY SOIC-8</td><td>39.4°C</td><td>70.0°C</td></tr> <tr><td>13</td><td>D42</td><td>SMD SFRD US1M 1A/1KV SMA t=2</td><td>39.1°C</td><td>69.5°C</td></tr> <tr><td>14</td><td>Q1</td><td>FET 2SK3673-01MR 10A/700V TO220F</td><td>46.5°C</td><td>78.5°C</td></tr> </tbody> </table>			NO	Position	PART NUMBER	ROOM AMBIENT Ta= 15.3°C	HIGH AMBIENT Ta= 48.3°C	1	LF1	TR1082 6-L2012-W902 18.9m GS	38.2°C	68.3°C	2	LF2	TR1083 W620 52~85m GSM60	40.6°C	71.2°C	3	BD1	BD 4A/800V GLASS UD4KB80	44.4°C	74.2°C	4	C5	120u/400V 105°C 18*31.5 VZ EPT	39.0°C	69.5°C	5	D1	RD 2A/800V GP20K T-52mm	49.3°C	79.8°C	6	C40	C/E 33u/50V UL10Kh 6.3*11 YXM	44.2°C	74.9°C	7	D40	RD 1A/1KV 1N4007GP T-52mm	43.9°C	74.7°C	8	T1coil	MT TF2495-R0 PQ-2620 GSM40-24 B	48.4°C	78.2°C	9	T1core	MT TF2495-R0 PQ-2620 GSM40-24 B	45.9°C	75.7°C	10	D100	SBD STPS20120CT 20A/120V TO220	53.3°C	82.4°C	11	C105	C/E 470u/35V UL7Kh 10*20 KY	43.7°C	73.6°C	12	U1	PWM FAN6756MRMY SOIC-8	39.4°C	70.0°C	13	D42	SMD SFRD US1M 1A/1KV SMA t=2	39.1°C	69.5°C	14	Q1	FET 2SK3673-01MR 10A/700V TO220F	46.5°C	78.5°C	P
NO	Position	PART NUMBER	ROOM AMBIENT Ta= 15.3°C	HIGH AMBIENT Ta= 48.3°C																																																																												
1	LF1	TR1082 6-L2012-W902 18.9m GS	38.2°C	68.3°C																																																																												
2	LF2	TR1083 W620 52~85m GSM60	40.6°C	71.2°C																																																																												
3	BD1	BD 4A/800V GLASS UD4KB80	44.4°C	74.2°C																																																																												
4	C5	120u/400V 105°C 18*31.5 VZ EPT	39.0°C	69.5°C																																																																												
5	D1	RD 2A/800V GP20K T-52mm	49.3°C	79.8°C																																																																												
6	C40	C/E 33u/50V UL10Kh 6.3*11 YXM	44.2°C	74.9°C																																																																												
7	D40	RD 1A/1KV 1N4007GP T-52mm	43.9°C	74.7°C																																																																												
8	T1coil	MT TF2495-R0 PQ-2620 GSM40-24 B	48.4°C	78.2°C																																																																												
9	T1core	MT TF2495-R0 PQ-2620 GSM40-24 B	45.9°C	75.7°C																																																																												
10	D100	SBD STPS20120CT 20A/120V TO220	53.3°C	82.4°C																																																																												
11	C105	C/E 470u/35V UL7Kh 10*20 KY	43.7°C	73.6°C																																																																												
12	U1	PWM FAN6756MRMY SOIC-8	39.4°C	70.0°C																																																																												
13	D42	SMD SFRD US1M 1A/1KV SMA t=2	39.1°C	69.5°C																																																																												
14	Q1	FET 2SK3673-01MR 10A/700V TO220F	46.5°C	78.5°C																																																																												
2	OVER LOAD BURN-IN TEST	NO DAMAGE 1 HOUR (MIN)	I/P : 230 VAC O/P : 129 % LOAD Ta : 25°C	TEST : OK	P																																																																											
3	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 2 HOUR	I/P : 264VAC/100VAC O/P : 100 % LOAD Ta= -34 °C	TEST : OK	P																																																																											
4	HIGH HUMIDITY HIGH TEMPERATURE HIGH VOLTAGE TURN ON TEST	AFTER 12 HOURS IN CHAMBER ON CONTROL 50 °C NO DAMAGE	I/P : 272 VAC O/P : FULL LOAD Ta= 50.2°C HUMIDITY= 95 %R.H	TEST : OK	P																																																																											
5	TEMPERATURE COEFFICIENT	± 0.03%/°C (0~50°C)	I/P : 230 VAC O/P : FULL LOAD	± 0.01%/°C (0~50°C)	P																																																																											
6	STORAGE TEMPERATURE TEST	<p>1. Thermal shock Temperature : -40°C~ +85°C</p> <p>2. Temperature change rate : 25°C / MIN</p> <p>3. Dwell time low and high temperature : 30 MIN/EACH</p> <p>4. Total test cycle : 5 CYCLE</p> <p>5. Input/Output condition : STATIC</p>			OK	P																																																																										
7	THERMAL SHOCK TEST	<p>1. Thermal shock Temperature : -30°C~ +60°C</p> <p>2. Temperature change rate : 25°C / MIN</p> <p>3. Dwell time low and high temperature : 30 MIN/EACH</p> <p>4. Total test cycle : 10 CYCLE</p> <p>5. Input/Output condition : 230VAC/Full Load AC ON/OFF TEST turn on 58sec ; turn off 2sec</p>			OK	P																																																																										



8	VIBRATION TEST	1 Carton & 1 Set (1) Waveform : Sine Wave (2) Frequency : 10~500Hz (3) Sweep Time : 12min/sweep cycle (4) Acceleration : 2G (5) Test Time : 60min in each axis (X.Y.Z) (6) Ta : 25°C	TEST : OK	P
9	CAPACITOR LIFE CYCLE	SUPPOSE C105 IS THE MOST CRITICAL COMPONENT (1) I/P : 230VAC O/P : FULL LOAD Ta= 25°C LIFE TIME (2) I/P : 230VAC O/P : FULL LOAD Ta= 50°C LIFE TIME (3) I/P : 230VAC O/P : 75% LOAD Ta= 50°C LIFE TIME (4) I/P : 230VAC O/P : 50% LOAD Ta= 50°C LIFE TIME	(1) 531677HRS (2) 66459HRS (3) 90703 HRS (4) 115626 HRS	P
10	MTBF	3613.2K hrs min. Telcordia SR-332 (Bellcore) ; 740.7K hrs min. MIL-HDBK-217F (25°C)		P
11	DMTBF/Accelerated Life Test	Demonstration Mean Time Between Failure (Expected Life): Above 30,000 hours @ TA 50°C		P

SAMPLE	TESTER	APPROVAL
PRODUCT SAMPLE	Shenym	WANGDZ

2007/3/20 A50-S014