



MODEL : NSD10-48D5

OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	RIPPLE & NOISE	V1: 75 mVp-p (Max) V2: 75 mVp-p (Max)	I/P: 48VDC O/P:FULL LOAD Ta:25°C	V1: 32 mVp-p (Max) V2: 16 mVp-p (Max)	P
2	OUTPUT VOLTAGE TOLERANCE	V1: 3 %- -3 % (Max) V2: 3 %- -3 % (Max)	I/P: 22VDC / 72VDC O/P:FULL/ MIN LOAD Ta:25°C	V1: 1.8 %- -1.8 % V2: 1.6 %- -1.6 %	P
3	LINE REGULATION	V1: 1%- -1 % (Max) V2: 1%- -1% (Max)	I/P: 22VDC ~ 72VDC O/P:FULL LOAD Ta:25°C	V1: 0.12 %- -0.12 % V2: 0 %- 0 %	P
4	LOAD REGULATION	V1: 2 %- -2 % (Max) V2: 2 %- -2 % (Max)	I/P: 48VDC O/P:FULL -MIN LOAD Ta:25°C	V1: 0.3 %- -0.3 % V2: 0.3 %- -0.3 %	P
5	CROSS REGULATION	V1: 2 %- -2 % (Max) V2: 2 %- -2 % (Max)	I/P: 48V VDC O/P: Testing O/P 60%LOAD Other O/P 40%LOAD Change Ta:25°C	V1: 1 %- -1 % V2: 1.2 %- -1.2 %	P
6	OVER/UNDERSHOOT TEST	< ±5%	I/P: 48 VDC O/P:FULL LOAD Ta:25°C	TEST: < 5 %	P
7	DYNAMIC LOAD	V1: 1000 mVp-p	I/P: 48VDC O/P:FULL /Min LOAD 90%DUTY/1KHZ Ta:25°C	207 mVp-p	P

INPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	INPUT VOLTAGE RANGE	22VDC~ 72 VDC	I/P:TESTING O/P:FULL LOAD Ta:25°C	14.6 V~ 72 V	P
			I/P: LOW-LINE-0.2V= 21.8 V HIGH-LINE+5%= 75.6 V O/P:FULL/MIN LOAD ON: 30 Sec . OFF: 30 Sec 10MIN (AC POWER ON/OFF NO DAMAGE)	TEST: OK	
2	EFFICIENCY	78 % (TYP)	I/P: 48 VDC O/P:FULL LOAD Ta:25°C	79.6 %	P
3	INPUT CURRENT	48 VDC/ 0.4A(TYP)	I/P: 48 VDC O/P:FULL LOAD Ta:25°C	I = 0.26 A	P
4	SHUTDOWN IDLE CURRENT	20 mA / 48VDC	I/P: 48 VDC O/P:FULL LOAD Ta:25°C	18.4 mA / 48VDC	P

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	OVER LOAD PROTECTION	Above 105%	I/P: 48VDC O/P: TESTING Ta: 25°C	157 % Over power Limiting, recovers automatically after fault condition is removed	P
2	OVER VOLTAGE PROTECTION	CH1: 5.75 V~ 7.5V CH2: -5.75 V~ -7.5V	I/P: DC SOURCE O/P: MIN LOAD Ta: 25°C	6.25V / CH1 / 0.17A 6.25 V / CH2 / 0.17A Recovers automatically after fault condition is removed	P
4	SHORT PROTECTION	SHORT EVERY OUTPUT 60 SECOND NO DAMAGE	I/P: 72 VDC O/P: FULL LOAD Ta: 25°C	NO DAMAGE Constant Current Limiting	P

CONTROL FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	REMOTE CONTROL	Logic "1" OPEN : ON Logic "0" GON : OFF	I/P: 48VDC O/P: FULL LOAD Ta: 25°C	Logic "1" : POWER ON Logic "0" : POWER OFF	P

ENVIRONMENT TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT																																																												
1	TEMPERATURE RISE TEST	MODEL : NSD10-48D5 1. ROOM AMBIENT BURN-IN : 1 HRS I/P: 48VDC O/P: FULL LOAD Ta= 25.9°C 2. HIGH AMBIENT BURN-IN : 1 HRS I/P: 48 VDC O/P: FULL LOAD Ta= 59.2 °C			P																																																												
		<table border="1"> <thead> <tr> <th>NO</th> <th>Position</th> <th>P/N</th> <th>ROOM AMBIENT Ta= 25.9 °C</th> <th>HIGH AMBIENT Ta= 59.2 °C</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>D100</td> <td>EC21QS04 2A/40V</td> <td>68.9°C</td> <td>99.0°C</td> </tr> <tr> <td>2</td> <td>D200</td> <td>EC21QS04 2A/40V</td> <td>70.6°C</td> <td>100.4°C</td> </tr> <tr> <td>3</td> <td>L100</td> <td>TS-027</td> <td>69.0°C</td> <td>99.8°C</td> </tr> <tr> <td>4</td> <td>C106</td> <td>33U/10V 125°C</td> <td>61.5°C</td> <td>91.9°C</td> </tr> <tr> <td>5</td> <td>C5</td> <td>474/100V 125°C</td> <td>64.2°C</td> <td>94.9°C</td> </tr> <tr> <td>6</td> <td>T1 COIL</td> <td>TS-015</td> <td>74.9°C</td> <td>106.5°C</td> </tr> <tr> <td>7</td> <td>Q1</td> <td>BCX56 1A/80V</td> <td>62.7°C</td> <td>93.2°C</td> </tr> <tr> <td>8</td> <td>Q2</td> <td>IRFR220N 5A/200V</td> <td>63.3°C</td> <td>94.0°C</td> </tr> <tr> <td>9</td> <td>L1</td> <td>3.3UH</td> <td>63.0°C</td> <td>93.7°C</td> </tr> <tr> <td>10</td> <td>U1</td> <td>TL3843</td> <td>71.1°C</td> <td>101.1°C</td> </tr> <tr> <td>11</td> <td>CASE</td> <td>上方中間處</td> <td>61.5°C</td> <td>91.6°C</td> </tr> </tbody> </table>	NO	Position		P/N	ROOM AMBIENT Ta= 25.9 °C	HIGH AMBIENT Ta= 59.2 °C	1	D100	EC21QS04 2A/40V	68.9°C	99.0°C	2	D200	EC21QS04 2A/40V	70.6°C	100.4°C	3	L100	TS-027	69.0°C	99.8°C	4	C106	33U/10V 125°C	61.5°C	91.9°C	5	C5	474/100V 125°C	64.2°C	94.9°C	6	T1 COIL	TS-015	74.9°C	106.5°C	7	Q1	BCX56 1A/80V	62.7°C	93.2°C	8	Q2	IRFR220N 5A/200V	63.3°C	94.0°C	9	L1	3.3UH	63.0°C	93.7°C	10	U1	TL3843	71.1°C	101.1°C	11	CASE	上方中間處	61.5°C	91.6°C		
NO	Position	P/N	ROOM AMBIENT Ta= 25.9 °C	HIGH AMBIENT Ta= 59.2 °C																																																													
1	D100	EC21QS04 2A/40V	68.9°C	99.0°C																																																													
2	D200	EC21QS04 2A/40V	70.6°C	100.4°C																																																													
3	L100	TS-027	69.0°C	99.8°C																																																													
4	C106	33U/10V 125°C	61.5°C	91.9°C																																																													
5	C5	474/100V 125°C	64.2°C	94.9°C																																																													
6	T1 COIL	TS-015	74.9°C	106.5°C																																																													
7	Q1	BCX56 1A/80V	62.7°C	93.2°C																																																													
8	Q2	IRFR220N 5A/200V	63.3°C	94.0°C																																																													
9	L1	3.3UH	63.0°C	93.7°C																																																													
10	U1	TL3843	71.1°C	101.1°C																																																													
11	CASE	上方中間處	61.5°C	91.6°C																																																													
2	OVER LOAD BURN-IN TEST	NO DAMAGE 1 HOUR (MIN)	I/P: 48VDC O/P: 120 % LOAD Ta:25°C	TEST : OK	P																																																												
3	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 2 HOUR	I/P: 48VDC O/P: 100 % LOAD Ta= -25 °C	TEST : OK	P																																																												
4	HIGH HUMIDITY HIGH TEMPERATURE HIGH VOLTAGE TURN ON TEST	AFTER 12 HOURS IN CHAMBER ON CONTROL 60 °C NO DAMAGE	I/P: 75VDC O/P:FULL LOAD Ta= 60 °C HUMIDITY= 95 %R.H	TEST : OK	P																																																												
5	TEMPERATURE COEFFICIENT	± 0.03 %(0~60°C)	I/P: 48 VDC O/P:FULL LOAD	± 0.012 %(0~60°C)	P																																																												
6	VIBRATION TEST	1 Carton & 1 Set (1) Waveform: Sine Wave (2) Frequency:10~500Hz (3) Sweep Time:10min/sweep cycle (4) Acceleration:2G (5) Test Time:1 hour in each axis (X.Y.Z) (6) Ta:25°C		TEST : OK	P																																																												

SAFETY TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P: 1.5KVDC/min	I/P-O/P: 1.8KVDC/min Ta:25°C	I/P-O/P: 0.002 mA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P:500VDC>100MΩ	I/P-O/P: 500 VDC Ta:25°C / 70% RH	I/P-O/P: 30GΩ NO DAMAGE	P
3	APPROVAL	TUV: Certificate NO : UL: File NO : E183223			P



E.M.C TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	RADIATION	EN55022 CLASS B	I/P: 48VDC O/P: FULL LOAD Ta: 25°C	PASS Test by certified Lab	P
2	E.S.D	EN61000-4-2 LIGHT INDUSTRY AIR: 8KV / Contact: 4KV	I/P: 48 VDC O/P: FULL LOAD Ta: 25°C	CRITERIA A	P
3	E.F.T	EN61000-4-4 LIGHT INDUSTRY INPUT: 1KV	I/P: 48 VDC O/P: FULL LOAD Ta: 25°C	CRITERIA A	P
7	Test by certified Lab & Test Report Prepare				

M.T.B.F & LIFE CYCLE CALCULATION

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	MTBF	MIL-HDBK-217F NOTICES2 PARTS COUNT TOTAL FAILURE RATE: 1878.5K HRS			P

COMPONENT STRESS TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	Power Transistor (D to S) or (C to E) Peak Voltage	Q2 Rated IRFR220N 5A/200V	I/P: High-Line +3V = 75 V O/P: (1) Full Load Turn on (2) Output Short Ta: 25°C	(1) 135 V (2) 170 V	P
2	Diode Peak Voltage	D100 Rated EC21QS04 2A/40V D200 Rated EC21QS04 2A/40V	I/P: High-Line +3V = 75 V O/P: (1) Full Load Turn on (2) Output Short Ta: 25°C	(1) 39.4 V (2) 26 V (1) 39.6 V (2) 30 V	P
3	Input Capacitor Voltage	C5 Rated : 474 / 100V	I/P: High-Line +3V = 75 V O/P: (1) Full Load Turn on /Off (2) Min load Turn on /Off (3) Full Load /Min load Change Ta: 25°C	(1) 74.85 V (2) 74.95 V (3) 74.95 V	P
4	Control IC Voltage Test	U1 Rated TL3843D : 20 V	I/P: High-Line +3V = 75 V O/P: (1) Full Load Turn on /Off (2) Min load Turn on /Off (3) Full Load /Min load Change Ta: 25°C	(1) 13.17 V (2) 9.96 V (3) 13.17 V	P

DATE	SAMPLE	TEST RESULT	TESTER	APPROVAL
2007/1/11	RD SAMPLE	PASS	VINCENT TSENG	MAX LIN
2007/3/5	PRODUCT SAMPLE W0702A48	PASS	VINCENT TSENG	MAX LIN
2007/5/24	PRODUCT SAMPLE W0705B71	PASS	VINCENT TSENG	MAX LIN

2003/12/12 A50-F023