



Test Report: RSP-2000-48

2000W Front End Power Supply

■ DESIGN VERIFY TEST

Output Function Test
Input Function Test
Protection Function Test
Control Function Test
Component Stress Test

■ SAFETY & E.M.C. TEST

Safety Test
E.M.C. Test

■ RELIABILITY TEST

ENVIRONMENT TEST

DESIGN VERIFY TEST

OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	RIPPLE & NOISE	V1: 300 mVp-p (Max)	I/P: 230VAC O/P:FULL LOAD Ta:25°C	V1: 152 mVp-p (Max)	P
2	OUTPUT VOLTAGE ADJUST RANGE	CH1: 42 V~ 56 V	I/P: 230 VAC I/P: 115 VAC O/P:MIN LOAD Ta:25°C	40.28 V~ 57.70 V/ 230 VAC 40.28 V~ 57.69 V/ 115 VAC	P
3	OUTPUT VOLTAGE TOLERANCE	V1: 1%~ -1 % (Max)	I/P: 180VAC / 264 VAC O/P:FULL/ MIN LOAD Ta:25°C	V1: 0.04 %~ -0.04 %	P
4	LINE REGULATION	V1:0.5 %~ -0.5% (Max)	I/P:180 VAC ~ 264 VAC O/P:FULL LOAD Ta:25°C	V1: 0 %~ 0 %	P
5	LOAD REGULATION	V1: 0.5 %~ -0.5 % (Max)	I/P: 230 VAC O/P:FULL ~MIN LOAD Ta:25°C	V1: 0.04 %~ -0.04 %	P
6	SET UP TIME	230VAC: 1500 ms (Max) 115 VAC: 1500 ms (Max)	I/P: 230 VAC @ FULL LOAD I/P: 115 VAC @80% LOAD Ta:25°C	230VAC/ 1163 ms 115VAC/ 1072 ms	P
7	RISE TIME	230VAC: 60 ms (Max) 115VAC: 60 ms (Max)	I/P: 230 VAC @ FULL LOAD I/P: 115 VAC @80% LOAD Ta:25°C	230VAC/ 37 ms 115VAC/ 36 ms	P
8	HOLD UP TIME	230VAC: 10 ms (TYP) 230VAC: 16 ms (TYP)	I/P: 230 VAC @ FULL LOAD I/P: 230 VAC @75% LOAD Ta:25°C	230VAC/ 18 ms 230VAC/ 22 ms	P
9	OVER/UNDERSHOOT TEST	< ±5%	I/P: 230 VAC O/P:FULL LOAD Ta:25°C	TEST: <5 %	P
10	DYNAMIC LOAD	V1: 4800 mVp-p	I/P: 230 VAC O/P:FULL /Min LOAD 90%DUTY/1KHZ Ta:25°C	393 mVp-p	P

INPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	INPUT VOLTAGE RANGE	180VAC~264 VAC	I/P:TESTING O/P:FULL LOAD Ta:25°C	149V~264V	P
			I/P: LOW-LINE-3V= 177V HIGH-LINE+15%=300 V O/P:FULL/MIN LOAD ON: 30 Sec . OFF: 30 Sec 10MIN (AC POWER ON/OFF NO DAMAGE)	TEST: OK	
2	INPUT FREQUENCY RANGE	47HZ ~63 HZ NO DAMAGE OSC	I/P: 180 VAC ~ 264 VAC O/P:FULL~MIN LOAD Ta:25°C	TEST: OK	P
3	POWER FACTOR	0.98 / 230 VAC(TYP)	I/P: 230 VAC O/P:FULL LOAD Ta:25°C	PF= 0.986 / 230 VAC	P
4	EFFICIENCY	92% (TYP)	I/P: 230 VAC O/P:FULL LOAD Ta:25°C	92.13%	P
5	INPUT CURRENT	230V/ 10 A (TYP) 115V/ 16 A (TYP)	I/P: 230 VAC @ full load I/P: 115 VAC @ 80% load Ta:25°C	I = 9.77 A/ 230 VAC I = 15.8 A/ 115 VAC	P
6	INRUSH CURRENT	230V/ 50 A (TYP)	I/P: 230 VAC O/P:FULL LOAD Ta:25°C	I = 30 A/ 230 VAC	P
7	LEAKAGE CURRENT	< 2 mA / 240 VAC	I/P: 240 VAC O/P:Min LOAD Ta:25°C	L-FG: 0.66 mA N-FG: 0.70 mA	P

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	OVER LOAD PROTECTION	105 %~ 125 %	I/P: 230 VAC I/P: 115 VAC O/P:TESTING Ta:25°C	110 %/ 230 VAC 110 %/ 115 VAC Constant Current Limiting, unit will shut down o/p voltage after 5 sec ,re-power on to recover.	P
2	OVER VOLTAGE PROTECTION	CH1: 57.6 V~ 67.2V	I/P: 230 VAC I/P: 115 VAC O/P:MIN LOAD Ta:25°C	60.70 V/ 230 VAC 60.57 V/ 115 VAC Shunt down Re- power ON	P
3	OVER TEMPERATURE PROTECTION	SPEC: TSW1: 80 ± 5°C O.T.P. TSW2: 75 ± 5°C O.T.P. NO DAMAGE	I/P: 230 VAC O/P:FULL LOAD	O.T.P. Active Shut down o/p voltage , recovers automatically after temperature goes down	P
4	SHORT PROTECTION	SHORT EVERY OUTPUT 1 HOUR NO DAMAGE	I/P: 264 VAC O/P:FULL LOAD Ta:25°C	NO DAMAGE Constant Current Limiting, unit will shut down o/p voltage after 5 sec ,re-power on to recover.	P

CONTROL FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT																												
1	AUXILIARY POWER (AUX)	5V @ 0.3A (4.5V~ 5.5V) 12V @ 0.8A (10.6V~13.2V)	I/P: 230 VAC O/P: FULL LOAD Ta: 25°C	5.302V 12.446V	P																												
2	REMOTE ON/OFF	ON/OFF/+5V-AUX SHORT : POWER OFF ON/OFF/+5V-AUX OPEN : POWER ON	I/P: 230 VAC O/P: FULL LOAD Ta: 25°C	SHORT : POWER OFF OPEN : POWER ON	P																												
3	REMOTE SENSE	Compensate voltage drop on the load wiring up to 0.5V	I/P: 230 VAC O/P: FULL LOAD Ta: 25°C	> 0.5 V	P																												
4	DC OK Signal	HIGH: VOUT ≤ 80±5%Vout LOW: VOUT ≥ 80±5%Vout	I/P: 230 VAC O/P: FULL LOAD Ta: 25°C	HIGH : <u>5.298 V</u> VO ≤ 79.16 %Vout LOW: <u>0 V</u> VO ≥ 82.58 %Vout	P																												
5	Output voltage TRIM	DC<0.4V Vo/p=100%±3% (0~100% load) DC=1V Vo/p=40%±3% (0~100% load) DC=2V Vo/p=60%±3% (0~100% load) DC=3V Vo/p=80%±3% (0~100% load) DC=4V Vo/p=100%±3% (0~100% load) DC=4.7V Vo/p=115%±3% (0~85.7% load)	I/P: 230 VAC <table border="1" data-bbox="767 869 1374 954"> <thead> <tr> <th>PV</th> <th><0.4V</th> <th>1V</th> <th>2V</th> <th>3V</th> <th>4V</th> <th>4.7V</th> </tr> </thead> <tbody> <tr> <td>48V</td> <td>100.3%</td> <td>41.54%</td> <td>58.70%</td> <td>78.42%</td> <td>99.18%</td> <td>115.29%</td> </tr> </tbody> </table>	PV	<0.4V	1V	2V	3V	4V	4.7V	48V	100.3%	41.54%	58.70%	78.42%	99.18%	115.29%	<table border="1" data-bbox="767 869 1374 954"> <thead> <tr> <th>PV</th> <th><0.4V</th> <th>1V</th> <th>2V</th> <th>3V</th> <th>4V</th> <th>4.7V</th> </tr> </thead> <tbody> <tr> <td>48V</td> <td>100.3%</td> <td>41.54%</td> <td>58.70%</td> <td>78.42%</td> <td>99.18%</td> <td>115.29%</td> </tr> </tbody> </table>	PV	<0.4V	1V	2V	3V	4V	4.7V	48V	100.3%	41.54%	58.70%	78.42%	99.18%	115.29%	P
PV	<0.4V	1V	2V	3V	4V	4.7V																											
48V	100.3%	41.54%	58.70%	78.42%	99.18%	115.29%																											
PV	<0.4V	1V	2V	3V	4V	4.7V																											
48V	100.3%	41.54%	58.70%	78.42%	99.18%	115.29%																											
6	OVER TEMP WARNING	T-ALARM TSW1 & TSW2 short(0~0.5V) TSW1 or TSW2 open(4.5V~5.5V)	I/P: 230 VAC O/P: FULL LOAD Ta: 25°C	TSW1 & TSW2 short : 0.004 V TSW1 or TSW2 open : 5.309 V	P																												
7	FAN SPEED CONTROL	<table border="1" data-bbox="411 1189 738 1323"> <thead> <tr> <th>Fan Speed</th> <th>Load</th> <th>PWM Duty</th> </tr> </thead> <tbody> <tr> <td>LOW</td> <td>0%</td> <td>10%±5%</td> </tr> <tr> <td>HIGH</td> <td>100%</td> <td>90%±5%</td> </tr> </tbody> </table>	Fan Speed	Load	PWM Duty	LOW	0%	10%±5%	HIGH	100%	90%±5%	I/P: 230 VAC O/P: TESTING Ta: 25°C	<table border="1" data-bbox="1007 1189 1334 1323"> <thead> <tr> <th>Fan Speed</th> <th>Load</th> <th>PWM Duty</th> </tr> </thead> <tbody> <tr> <td>LOW</td> <td>0%</td> <td>10.50%</td> </tr> <tr> <td>HIGH</td> <td>100%</td> <td>90.21%</td> </tr> </tbody> </table>	Fan Speed	Load	PWM Duty	LOW	0%	10.50%	HIGH	100%	90.21%	P										
Fan Speed	Load	PWM Duty																															
LOW	0%	10%±5%																															
HIGH	100%	90%±5%																															
Fan Speed	Load	PWM Duty																															
LOW	0%	10.50%																															
HIGH	100%	90.21%																															
8	CURRENT SHARING	PSU1-PSU2 < 10%	I/P : 230 VAC O/P : 100%/50% LOAD Ta : 25°C	O/P : 100% LOAD PSU1 : 42A PSU2 : 42A PSU3 : 42A PSU4 : 42A O/P : 50% LOAD PSU1 : 20.4A PSU2 : 21.5A PSU3 : 21.1A PSU4 : 21.1A	P																												

ENVIRONMENT TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT																																																																																																																													
1	TEMPERATURE RISE TEST	MODEL : RSP-2000-24 1. ROOM AMBIENT BURN-IN : 3.5HRS I/P: 230VAC O/P: FULL LOAD Ta=33.3℃ 2. HIGH AMBIENT BURN-IN : 3HRS I/P: 230VAC O/P: FULL LOAD Ta=52.4℃																																																																																																																																
				<table border="1"> <thead> <tr> <th>NO</th> <th>Position</th> <th>P/N</th> <th>ROOM AMBIENT Ta= 33.3℃</th> <th>HIGH AMBIENT Ta= 52.4℃</th> </tr> </thead> <tbody> <tr><td>1</td><td>BD1</td><td>30A/800V SILICON US30KB80R</td><td>56.2℃</td><td>76.0℃</td></tr> <tr><td>2</td><td>Q603</td><td>STP30N65M5 22A/650V TO220</td><td>45.1℃</td><td>62.3℃</td></tr> <tr><td>3</td><td>L1</td><td>TR931</td><td>41.5℃</td><td>58.5℃</td></tr> <tr><td>4</td><td>C5</td><td>330u/400V 105℃ 30*30 VXH</td><td>42.9℃</td><td>61.2℃</td></tr> <tr><td>5</td><td>U1</td><td>TOP256EN</td><td>43.8℃</td><td>63.0℃</td></tr> <tr><td>6</td><td>Q903</td><td>FCP22N60N 22A/600V TO220</td><td>50.9℃</td><td>71.9℃</td></tr> <tr><td>7</td><td>T1</td><td>TF2093-R1</td><td>55.0℃</td><td>73.4℃</td></tr> <tr><td>8</td><td>T2</td><td>TF2094-R1</td><td>67.5℃</td><td>87.0℃</td></tr> <tr><td>9</td><td>U2</td><td>UCC28220D SOIC-16</td><td>49.4℃</td><td>69.5℃</td></tr> <tr><td>10</td><td>Q101</td><td>FDP090N10 75A/100V TO220</td><td>52.4℃</td><td>71.5℃</td></tr> <tr><td>11</td><td>Q105</td><td>FDP090N10 75A/100V TO220</td><td>63.1℃</td><td>83.1℃</td></tr> <tr><td>12</td><td>D110</td><td>M6060C 60A/60V TO220</td><td>61.1℃</td><td>80.7℃</td></tr> <tr><td>13</td><td>Q533</td><td>PSMN2R6-40YS 100A/40V LPAK</td><td>58.2℃</td><td>78.4℃</td></tr> <tr><td>14</td><td>C73</td><td>47u/25V L5Kh 5*11 KY</td><td>44.7℃</td><td>63.6℃</td></tr> <tr><td>15</td><td>T3</td><td>TF2100-R1</td><td>48.8℃</td><td>71.7℃</td></tr> <tr><td>16</td><td>C320</td><td>470u/25V UL7Kh 8*20 KY</td><td>48.0℃</td><td>67.0℃</td></tr> <tr><td>17</td><td>RG300</td><td>YS065W WS-AP017</td><td>47.3℃</td><td>66.3℃</td></tr> <tr><td>18</td><td>C325</td><td>100u/25V L5Kh 6.3*11 KY</td><td>49.0℃</td><td>68.4℃</td></tr> <tr><td>19</td><td>C301</td><td>1500u/16V UL10Kh 10*20 ZLH</td><td>46.3℃</td><td>65.4℃</td></tr> <tr><td>20</td><td>L100</td><td>TF2098-R3</td><td>58.4℃</td><td>79.1℃</td></tr> <tr><td>21</td><td>C110</td><td>1500u/35V UL10Kh 12.5*30 ZLH</td><td>57.0℃</td><td>77.0℃</td></tr> <tr><td>22</td><td>C115</td><td>1500u/35V UL10Kh 12.5*30 ZLH</td><td>52.6℃</td><td>72.4℃</td></tr> <tr><td>23</td><td>TSW8</td><td>ST-22W-R0 80℃ 100mm HH(H110)</td><td>54.4℃</td><td>73.7℃</td></tr> <tr><td>24</td><td>TSW9</td><td>ST-22W-R0 80℃ 55mm HH(H110)</td><td>51.5℃</td><td>68.6℃</td></tr> </tbody> </table>	NO	Position	P/N	ROOM AMBIENT Ta= 33.3℃	HIGH AMBIENT Ta= 52.4℃	1	BD1	30A/800V SILICON US30KB80R	56.2℃	76.0℃	2	Q603	STP30N65M5 22A/650V TO220	45.1℃	62.3℃	3	L1	TR931	41.5℃	58.5℃	4	C5	330u/400V 105℃ 30*30 VXH	42.9℃	61.2℃	5	U1	TOP256EN	43.8℃	63.0℃	6	Q903	FCP22N60N 22A/600V TO220	50.9℃	71.9℃	7	T1	TF2093-R1	55.0℃	73.4℃	8	T2	TF2094-R1	67.5℃	87.0℃	9	U2	UCC28220D SOIC-16	49.4℃	69.5℃	10	Q101	FDP090N10 75A/100V TO220	52.4℃	71.5℃	11	Q105	FDP090N10 75A/100V TO220	63.1℃	83.1℃	12	D110	M6060C 60A/60V TO220	61.1℃	80.7℃	13	Q533	PSMN2R6-40YS 100A/40V LPAK	58.2℃	78.4℃	14	C73	47u/25V L5Kh 5*11 KY	44.7℃	63.6℃	15	T3	TF2100-R1	48.8℃	71.7℃	16	C320	470u/25V UL7Kh 8*20 KY	48.0℃	67.0℃	17	RG300	YS065W WS-AP017	47.3℃	66.3℃	18	C325	100u/25V L5Kh 6.3*11 KY	49.0℃	68.4℃	19	C301	1500u/16V UL10Kh 10*20 ZLH	46.3℃	65.4℃	20	L100	TF2098-R3	58.4℃	79.1℃	21	C110	1500u/35V UL10Kh 12.5*30 ZLH	57.0℃	77.0℃	22	C115	1500u/35V UL10Kh 12.5*30 ZLH	52.6℃	72.4℃	23	TSW8	ST-22W-R0 80℃ 100mm HH(H110)	54.4℃	73.7℃	24	TSW9	ST-22W-R0 80℃ 55mm HH(H110)	51.5℃	68.6℃	P
NO	Position	P/N	ROOM AMBIENT Ta= 33.3℃	HIGH AMBIENT Ta= 52.4℃																																																																																																																														
1	BD1	30A/800V SILICON US30KB80R	56.2℃	76.0℃																																																																																																																														
2	Q603	STP30N65M5 22A/650V TO220	45.1℃	62.3℃																																																																																																																														
3	L1	TR931	41.5℃	58.5℃																																																																																																																														
4	C5	330u/400V 105℃ 30*30 VXH	42.9℃	61.2℃																																																																																																																														
5	U1	TOP256EN	43.8℃	63.0℃																																																																																																																														
6	Q903	FCP22N60N 22A/600V TO220	50.9℃	71.9℃																																																																																																																														
7	T1	TF2093-R1	55.0℃	73.4℃																																																																																																																														
8	T2	TF2094-R1	67.5℃	87.0℃																																																																																																																														
9	U2	UCC28220D SOIC-16	49.4℃	69.5℃																																																																																																																														
10	Q101	FDP090N10 75A/100V TO220	52.4℃	71.5℃																																																																																																																														
11	Q105	FDP090N10 75A/100V TO220	63.1℃	83.1℃																																																																																																																														
12	D110	M6060C 60A/60V TO220	61.1℃	80.7℃																																																																																																																														
13	Q533	PSMN2R6-40YS 100A/40V LPAK	58.2℃	78.4℃																																																																																																																														
14	C73	47u/25V L5Kh 5*11 KY	44.7℃	63.6℃																																																																																																																														
15	T3	TF2100-R1	48.8℃	71.7℃																																																																																																																														
16	C320	470u/25V UL7Kh 8*20 KY	48.0℃	67.0℃																																																																																																																														
17	RG300	YS065W WS-AP017	47.3℃	66.3℃																																																																																																																														
18	C325	100u/25V L5Kh 6.3*11 KY	49.0℃	68.4℃																																																																																																																														
19	C301	1500u/16V UL10Kh 10*20 ZLH	46.3℃	65.4℃																																																																																																																														
20	L100	TF2098-R3	58.4℃	79.1℃																																																																																																																														
21	C110	1500u/35V UL10Kh 12.5*30 ZLH	57.0℃	77.0℃																																																																																																																														
22	C115	1500u/35V UL10Kh 12.5*30 ZLH	52.6℃	72.4℃																																																																																																																														
23	TSW8	ST-22W-R0 80℃ 100mm HH(H110)	54.4℃	73.7℃																																																																																																																														
24	TSW9	ST-22W-R0 80℃ 55mm HH(H110)	51.5℃	68.6℃																																																																																																																														
2	OVER LOAD BURN-IN TEST	NO DAMAGE 1 HOUR (MIN)	I/P: 230 VAC O/P: 108 % LOAD Ta:25℃	TEST : OK	P																																																																																																																													
3	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 2 HOUR	I/P: 230 VAC O/P: 100% LOAD Ta= -35℃	TEST : OK	P																																																																																																																													
4	HIGH HUMIDITY HIGH TEMPERATURE HIGH VOLTAGE TURN ON TEST	AFTER 12 HOURS IN CHAMBER ON CONTROL 50 ℃ NO DAMAGE	I/P: 272 VAC O/P: FULL LOAD Ta= 50℃ HUMIDITY= 95 %R.H	TEST : OK	P																																																																																																																													
5	TEMPERATURE COEFFICIENT	± 0.03 % (0~50℃)	I/P: 230 VAC O/P: FULL LOAD	± 0.003 % (0~50℃)	P																																																																																																																													

6	VIBRATION TEST	1 Carton & 1 Set (1) Waveform: Sine Wave (2) Frequency:10~500Hz (3) Sweep Time:10min/sweep cycle (4) Acceleration:2G (5) Test Time:1 hour in each axis (X.Y.Z) (6) Ta:25°C	TEST : OK	P
---	----------------	--	-----------	---

SAFETY TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P: 3 KVAC/min I/P-FG: 1.5 KVAC/min O/P-FG: 0.5 KVAC/min	I/P-O/P: 3.6 KVAC/min I/P-FG: 1.8 KVAC/min O/P-FG: 0.6 KVAC/min Ta:25°C	I/P-O/P: 9.37 mA I/P-FG: 7.49 mA O/P-FG: 7.13 mA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P:500VDC>100MΩ I/P-FG: 500VDC>100MΩ O/P-FG:500VDC>100MΩ	I/P-O/P: 500 VDC I/P-FG: 500 VDC O/P-FG: 500 VDC Ta:25°C	I/P-O/P: 7.8 GΩ I/P-FG: 7.79 GΩ O/P-FG: 12.1 GΩ NO DAMAGE	P
3	GROUNDING CONTINUITY	FG(PE) TO CHASSIS OR TRACE < 100 mΩ	40 A / 2min Ta:25°C	6 mΩ	P

E.M.C TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	HARMONIC	EN61000-3-2 CLASS A CLASS D	I/P: 220/230/240 VAC/60HZ O/P:100%75%50%25% LOAD Ta:25°C	PASS	P
2	CONDUCTION	EN55022 CLASS B	I/P: 230 VAC (50HZ) O/P:FULL/50% LOAD Ta:25°C	PASS Test by certified Lab	P
3	RADIATION	EN55022 CLASS A	I/P: 230 VAC (50HZ) O/P:FULL LOAD Ta:25°C	PASS Test by certified Lab	P
4	E.S.D	EN61000-4-2 INDUSTRY AIR:8KV / Contact:4KV	I/P: 230 VAC/50HZ O/P:FULL LOAD Ta:25°C	CRITERIA A	P
5	E.F.T	EN61000-4-4 INDUSTRY INPUT: 2KV	I/P: 230 VAC/50HZ O/P:FULL LOAD Ta:25°C	CRITERIA A	P
6	SURGE	IEC61000-4-5 INDUSTRY L-N :2KV L,N-PE:4KV	I/P: 230 VAC/50HZ O/P:FULL LOAD Ta:25°C	CRITERIA A	P
7	Test by certified Lab & Test Report Prepare				

M.T.B.F & LIFE CYCLE CALCULATION

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	CAPACITOR LIFE CYCLE	RSP-2000-24 : SUPPOSE C110 IS THE MOST CRITICAL COMPONENT I/P: 230VAC O/P:FULL LOAD Ta= 25 °C LIFE TIME=595726 HRS I/P: 230VAC O/P:FULL LOAD Ta= 50 °C LIFE TIME=98887 HRS I/P: 230VAC O/P:75% LOAD Ta= 50 °C LIFE TIME=173473 HRS I/P: 230VAC O/P:50% LOAD Ta= 50 °C LIFE TIME=259367 HRS			P
2	MTBF	Conducted by Parts Stress Analysis Prediction 487.7K hrs min. Telcordia SR-332 (Bellcore) ; 42.9K hrs min. MIL-HDBK-217F (25°C)			P
3	DMTBF/Accelerated Life Test	Demonstration Mean Time Between Failure : Above 30,000 hours @ TA 50°C			P

COMPONENT STRESS TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	Power Transistor (D to S) or (C to E) Peak Voltage	Q900 Rated FCP22N60N 22A/600V	I/P : High-Line +3V = 267 V O/P : (1)Full Load Turn on (2) Output Short (3)Full load continue Ta : 25°C	(1) 460 V (2) 454 V (3) 444 V	P
2	Diode Peak Voltage	Q100 Rated IRFB4227PbF 65A/200V	I/P : High-Line +3V = 267 V O/P : (1)Full Load Turn on (2) Output Short (3)Full load continue Ta : 25°C	(1) 198 V (2) 147 V (3) 198 V	P
		Q103 Rated IRFB4227PbF 65A/200V	I/P : High-Line +3V = 267 V O/P : (1)Full Load Turn on (2) Output Short (3)Full load continue Ta : 25°C	(1) 198 V (2) 106 V (3) 161 V	P
3	Input Capacitor Voltage	C5 Rated 330u/400V 105°C 30*30 VXH	I/P:High-Line +3V = 267 V O/P: (1)Full Load Turn on /Off (2) Min load Turn on /Off (3)Full Load /Min load Change Ta:25°C	(1) 377.64 V (2) 378.56 V (3) 386.24 V	P
4	Control IC Voltage Test	U2 Rated PWM UCC28220D 8.4V~14.5V	I/P:High-Line +3V = 267 V O/P: (1)Full Load Turn on /Off (2) Min load Turn on /Off (3)Full Load /Min load Change Ta:25°C	(1) 13.051 V (2) 11.868 V (3) 13.204 V	P
5	Power Transistor (D to S) or (C to E) Peak Voltage	Q603 Rated S1P30N65M5 22A/650V	I/P : High-Line +3V = 267 V O/P : (1)Full Load Turn on (2) Output Short (3)Full load continue Ta : 25°C	(1) 464 V (2) 456 V (3) 442 V	P

DATE	SAMPLE	TEST RESULT	TESTER	APPROVAL
	RD SAMPLE	PASS		VINCENT TSENG
	PRODUCT SAMPLE	PASS		VINCENT TSENG
	PRODUCT SAMPLE	PASS		VINCENT TSENG

2003/12/12 A50-F023